

# ANNEX F1

CALIBRATION CERTIFICATES FOR SURFACE WATER QUALITY MONITORING EQUIPMENT



ALS Technichem (HK) Pty Ltd 11/F., Chung Shun Knitting Centre, 1 - 3 Wing Yip Street, Kwai Chung, N.T., Hong Kong T: +852 2610 1044 F: +852 2610 2021 www.alsglobal.com

# **REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION**

CONTACT: CLIENT:	MR IVAN LEUNG ALS TECHNICHEM (HK) PTY LTD	WORK ORDER:	HK2417116
ADDRESS:	11/F., CHUNG SHUN KNITTING CENTRE,	SUB-BATCH:	0
	1-3 WING YIP STREET, KWAI CHUNG, N.T.	LABORATORY:	HONG KONG
		DATE RECEIVED:	03-May-2024
		DATE OF ISSUE:	10-May-2024

## **GENERAL COMMENTS**

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

## EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.			
Equipment Type:	Multifunctional Meter		
Service Nature:	Performance Check		
Scope:	Conductivity, Dissolved Oxygen, pH Value, Turbidity, Salinity and Temperature		
Brand Name/ Model No.:	[HORIBA]/ [U-52G]		
Serial No./ Equipment No.:	[NVAE08GT]/ [N/A]		
Date of Calibration:	09-May-2024		

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

# **REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION**



WORK ORDER: HK2417116 **SUB-BATCH:** 0 DATE OF ISSUE: 10-May-2024 **CLIENT:** ALS TECHNICHEM (HK) PTY LTD Multifunctional Meter Equipment Type: Brand Name/ [HORIBA]/[U-52G] Model No.: Serial No./ [NVAE08GT]/ [N/A] Equipment No.: Date of Next Calibration: Date of Calibration: 09-May-2024 09-August-2024

### PARAMETERS:

#### Conductivity Method Ref: APHA (23rd edition), 2510B

· · ·			
Expected Reading (µS/cm)	Displayed Reading (µS/cm)	Tolerance (%)	
146.9	135	-8.1	
6667	6470	-3.0	
12890	12300	-4.6	
58670	54200	-7.6	
	Tolerance Limit (%)	±10.0	

#### **Dissolved Oxygen**

#### Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.62	2.61	-0.01
5.85	5.82	-0.03
7.21	7.32	+0.11
	Tolerance Limit (mg/L)	±0.20

#### pH Value

#### Method Ref: APHA (23rd edition), 4500H: B

Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)	
4.0	3.86	-0.14	
7.0	7.04	+0.04	
10.0	10.01	+0.01	
	Tolerance Limit (pH unit)	±0.20	

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

# **REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION**



WORK ORDER: HK2417116 **SUB-BATCH:** 0 DATE OF ISSUE: 10-May-2024 **CLIENT:** ALS TECHNICHEM (HK) PTY LTD Equipment Type: Multifunctional Meter Brand Name/ [HORIBA]/[U-52G] Model No.: Serial No./ [NVAE08GT]/ [N/A] Equipment No.: Date of Calibration: Date of Next Calibration: 09-May-2024 09-August-2024

### PARAMETERS:

Turbidity

#### Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.0	
4	3.7	-7.5
40	37.2	-7.0
80	75.3	-5.9
400	371	-7.3
800	805	+0.6
	Tolerance Limit (%)	±10.0

Salinity

#### Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)	
0	0.01		
10	9.85	-1.5	
20	19.23	-3.9	
30	29.04	-3.2	
	Tolerance Limit (%)	±10.0	

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

# **REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION**

WORK ORDER:	HK2417116			(ALS)
SUB-BATCH: DATE OF ISSUE: CLIENT:	0 10-May-2024 ALS TECHNICHEM (HK) PTY LTE	)		
Equipment Type: Brand Name/ Model No.: Serial No./ Equipment No.:	Multifunctional Meter [HORIBA]/ [U-52G] [NVAE08GT]/ [N/A]			
Date of Calibration:	09-May-2024	Date of Next Calibration:	09-August-2024	

## PARAMETERS:

#### Temperature

#### Method Ref: Section 6 of International Accreditation New Zealand Technical Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)	
14.5	14.13	-0.4	
23.5	24.02	+0.5	
40.0	39.72	-0.3	
	Tolerance Limit (°C)	±2.0	

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics